


Downlight empotrable LED redondo Belur 18W Blanco



Referencia	201000097	201000098	201000099
Potencia (W) con difusor/ luminaria	18W	18W	18W
Flujo luminoso (Lm) con difusor/luminaria	1.620Lm	1.620Lm	1.620Lm
Temperatura (K)	3.000K	4.000K	6.500K
Temperatura funcionamiento (°C)	+40°C -20°C	40°C	40°C
Ángulo apertura (°)	120°	120°	120°
Tiempo de encendido	<0.5	<0.5	<0.5
CRI	80	80	80
On/Off	50.000	50.000	50.000
Horas de vida	15.000h.	15.000h.	15.000h.
Amperios (mA)	160mA	160mA	160mA
IP	IP20	IP20	IP20
IK	IK4	IK4	IK4
Uso	Interior	Interior	Interior
Driver reemplazable	No	No	No
Luminaria LED reemplazable	No	No	No
Material principal	Plástico	Plástico	Plástico
Color principal	Blanco	Blanco	Blanco
Profundidad empotramiento (mm)	27mm	27mm	27mm
Empotramiento (Rango)	Ø195-210mm	Ø195-210mm	Ø195-210mm
Diámetro (mm) (Ø)	Ø220mm	Ø220mm	Ø220mm
Voltaje (V)	220-240V	220-240V	220-240V
Hz	50/60Hz	50/60Hz	50/60Hz



A: Ø220mm
B: 27mm
C: Ø195-210mm

**Downlight empotrable
LED redondo Belur
18W 3000K Blanco**

